


**FLUKE®**






**It's time to SEE WHAT YOU'RE MISSING**

**THE EXPERT SERIES**

# The FUTURE OF INFRARED is here.





*Your work as an expert thermographer is defined by the quality of the infrared images you take and your ability to analyze what's before you. The most pressing challenge lies not in analyzing what you see, but the fear of missing something you can't.*

\* HD images are captured by the TiX1000 in SuperResolution mode and viewable in the SmartView® software.

# Introducing THE EXPERT SERIES

**The right cameras when you can't afford to be wrong.**

Instantly capture highly detailed images and start analyzing them while still in the field.


See incredible detail from a distance or extremely close up.

Capture tough shots with the largest LCD displays with Fluke Connect™



## **SuperResolution: The most spectacular images ever from a Fluke infrared camera.**

Select the SuperResolution mode before you capture images and transfer them to the included SmartView® software to reveal up to 3.1 million pixels (use the TiX1000 and SuperResolution to produce HD quality imagery)—4x the on-camera standard resolution and see infrared in a whole new way.



Step 1.

Step 2.

Step 3.

Step 4.


### **How does it work?**

An infrared image consists of sensitive elements and the blank or non-sensitive spaces between them.

SuperResolution shifts the sensitive elements 4x and fills the spaces, resulting in 100% coverage and an image with 4x more resolution.

# The industry's most advanced focus options.

Get through your day faster. The advanced focus systems in these cameras take in-focus images faster and easier providing premium image quality and precise temperature readings.




Chain link fence Target

## LaserSharp® Auto Focus.

Get an in-focus image like never before with just a touch of a button. LaserSharp® Auto Focus, exclusive to Fluke, uses its built-in laser distance meter to calculate and display the distance to your designated target with pinpoint accuracy. On target and in-focus. Every. Single. Time.

*Available on TiX1000/X660/X560/X520*



## EverSharp multi-focus recording for edge-to-edge clarity.

Capture multiple images from varying focal distances to get the best image possible. Using special algorithms, SmartView® software combines those images and creates one image with sharpened details of your target.

*Available on TiX1000/X660/X640*




Image sharpening **off**





Image sharpening **on**

## Image sharpening

Get premium images in high temp applications by combining multiple frames of data into one with image sharpening.

*Available on TiX560*



## Subwindowing helps identify failures in the lab before they become failures in the field.

Capture, document and analyze multiple frames of data per second to see sudden temperature changes in critical product development and quality control applications.

*Available on TiX1000/X660/X640*

## THE EXPERT SERIES

TiX1000/X660/X640

# Fluke TiX1000, TiX660 and TiX640 Infrared Camera

## Work from safer distances

Inspect areas that you could not get close to before and still get spectacular, detailed infrared images.



TiX660

### TiX1000

The FIRST HD\* infrared camera with Fluke Connect™  
10x more on-camera pixels than standard 320 x 240 infrared cameras  
1024 x 768 resolution (786,432 pixels)

### TiX660 and TiX640

4x more on-camera pixels than standard 320 x 240 infrared cameras  
640 x 480 resolution (307,200 pixels)

#### 1 Save time and get consistently in-focus images

With LaserSharp® Auto Focus, (TiX1000/X660 only) auto focus, manual, and EverSharp multifocal recording—the most advanced focus options all in one camera.

#### 2 Enhanced image quality and temperature measurement accuracy

Details come to life with 4x greater resolution than standard mode with SuperResolution (3.1 million pixels).

#### 3 Optimized for outdoor inspections

Viewfinder reduces outdoor glare for fast and easy image capture. (TiX1000/X660 only)



TiX640

**4 Large, adjustable 5.6 inch display for premium viewing**

Get a premium in-field viewing experience for quick issue identification with the large 5.6-inch high resolution LCD screen. Easily navigate over, under and around objects to get the best picture.



**5 Choose the most convenient image transfer protocol for your application**

Camera data ports: SD card, GigE Vision, RS-232, USB 2.0, DVI-D and composite video. SmartView® software: SD card (GigE Vision and RS-232)

**6 Help identify failures in the lab before they become failures in the field**

Track rapid changes in temperature with optional Subwindowing features. Capture, document and analyze multiple frames of data per second in product development and quality control (eg. printed circuit board production).

**8 User defined programmable buttons**

Program one-touch access for most used features.

**9 More lenses, More options. Better results.**

Optional lenses for maximum versatility (2 wide angle, 3 macro and 2x and 4x telephoto lenses)

**7 See it. Save it. Share it**

See what your team is seeing, watch live video and readings to troubleshoot problems, get questions answered and work orders approved before you leave the field.

TiX1000	TiX660/TiX640
Option 1: 640 x 480 (60 fps)	Option 1: 384 x 288 (120 fps)
Option 2: 384 x 288 (120 fps)	Option 2: 640 x 120 (240 fps)
Option 3: 1024 x 96 (240 fps)	

\*HD images are captured by the TiX1000 in SuperResolution mode and viewable in the SmartView® software.  
 \*\*Fluke Connect is not available in all countries.  
 \*\*\*Within your providers wireless service area

## Fluke TiX560 and TiX520 Infrared Cameras

# Your view of infrared technology is about to change 180°

Easily annotate, edit and analyze images with the largest 5.7 inch touchscreen LCD in its class.<sup>4</sup>



TiX560

### TiX560

Remote control  
High temperature measurements up to 1200° C  
On-camera post image editing  
Turn your 320 x 240 images into 640 x 480 images with SuperResolution mode *(available on camera and in software)*

### TiX520

On-camera post image editing  
Turn your 320 x 240 images into 640 x 480 images with SuperResolution mode *(available in software)*

#### 1 Easy navigation

Easily navigate over, under and around objects with the 180° articulating lens and see the image before you capture it.

#### 2 More lenses. More options. Better results.

Get the best image possible with optional field installable telephoto and wide angle lens. Bring small and distance objects closer with a telephoto lens, or widen your field in view in tight spaces with a wide angle lens.

#### 3 Enhanced image quality and temperature measurement accuracy

Turn your 320 x 240 images into 640 x 480 images, 4x's the resolution and pixels with SuperResolution.

#### 4 Save time and get consistently in-focus images

With LaserSharp® Auto Focus—uses a built-in laser distance meter that calculates and displays the distance to your designated target<sup>1</sup> and optional manual focus.

**5 On camera analytics**

Save time with post-capture image editing—edit emissivity, background temperature, transmissivity, palettes, color alarms, IR-Fusion® and enable/disable markers from the field.

**6 Get premium image output in high temp applications**

By combining multiple sequential frames of data into one with image sharpening.

**7 Find subtle temperature differences easier**

Instantly improve thermal sensitivity from 45 mK to 30 mK in the TiX560 and from 50 mK to 40 mK in the TiX520 with filter mode.



**8 IR-Fusion® Technology**

Our patented technology blends digital and infrared images into a single image to precisely document problem areas.

**9 See it. Save it. Share it with the Fluke Connect™ app<sup>2</sup>**

See what your team is seeing, watch live video and readings to troubleshoot problems, get questions answered and approve work orders from the field.<sup>3</sup>

**10 Large, adjustable 5.7 inch display**

Get a premium in-field viewing experience with the only 5.7 inch responsive touchscreen LCD in its class<sup>4</sup>—150% more viewing area<sup>5</sup>.

<sup>1</sup> Up to 30 meters (100 feet). <sup>2</sup> Fluke Connect is not available in all countries. <sup>3</sup> Within your providers wireless service area. <sup>4</sup> Compared to industrial handheld infrared cameras with 320 x 240 detector resolution as of October 14, 2014. <sup>5</sup> Compared to a 3.5 inch screen.

# THE EXPERT SERIES

## Specifications



	TiX1000	TiX660	TiX640	TiX560	TiX520
<b>IFOV (spatial resolution)</b>	0.6 mRad	0.8 mRad		1.3 mRad	
<b>Detector resolution</b>	1024 x 768 (786,432 pixels) SuperResolution mode: 2048 x 1536 (3.1 million pixels)	640 x 480 (307,200 pixels) SuperResolution mode: 1280 x 960 (1.2 million pixels)	640 x 480 (307,200 pixels)	320 x 240 (76,800 pixels)	
<b>Field of view</b>	32.4° x 24.7°	30.9° x 23.1°		24 °H x 17 °V	
<b>Optional lenses</b>	Capture spectacular images close up or from a distance with optional lenses: 2 wide angle, 2 telephoto, 3 macro and 1 standard			Optional telephoto and wide angle lenses	
<b>Wireless connectivity</b>	Fluke Connect™ app compatible with Fluke Connect® WiFi SD Card <sup>1</sup>			Fluke Connect™ app compatible with built-in Fluke Connect WiFi	
<b>Focus system</b>	LaserSharp® Auto Focus, auto focus, manual focus, and EverSharp multifocal recording		Auto focus, manual focus, and EverSharp multifocal recording	LaserSharp® Auto Focus with built-in laser distance meter and advanced manual focus	
<b>IR-Fusion® technology/ Visible context</b>	IR-Fusion® AutoBlend mode Picture-in-picture, color alarms (above and below user defined temperatures)				
<b>Display</b>	Extra-large 5.6 inch color TFT display, 1280 x 800 pixel resolution, Suitable for daylight operation			5.7 inch touchscreen LCD, 640 x 480 pixel resolution	
<b>Design</b>	Camcorder with handle, Tilttable LCoS color viewfinder display for outdoor use, 800 × 600 pixel resolution		Camcorder	Ergonomic FlexCam design with a 180 degree articulating lens	
<b>Thermal sensitivity</b>	≤ 0.05 °C at 30 °C target temp (50 mK)	≤ 0.03 °C at 30 °C target temp (30 mK)		≤ 0.045 °C at 30 °C target temp (45 mK); Filter Mode (NETD improvement) ≤ 0.03 °C at 30 °C target temp (30 mK)	≤ 0.05 °C at 30 °C target temp (50 mK); Filter Mode (NETD improvement) ≤ 0.04 °C at 30 °C target temp (40 mK)
<b>Temperature measurement range</b>	-40 °C to +1200 °C (-40 °F to +2192 °F) High temperature option: up to 2000°C (3632 °F)		-40 °C to +1200 °C (-40 °F to +2192 °F)	-20 °C to +1200 °C (-4 °F to +2192 °F)	-20 °C to +850 °C (-4 °F to +1562 °F)
<b>Frame rate</b>	30 Hz or 9 Hz versions		60 Hz or 9 Hz versions		
<b>Subwindowing modes<sup>2</sup></b>	Option 1: 640 x 480 (60 fps) Option 2: 384 x 288 (120 fps) Option 3: 1024 x 96 (240 fps)	Option 1: 384 x 288 (120 fps) Option 2: 640 x 120 (240 fps)		—	
<b>Software</b>	SmartView® software and Fluke Connect™ <sup>1</sup>				
<b>Voice annotation</b>	Yes				
<b>Text annotation</b>	Yes				
<b>Video recording</b>	Standard and radiometric				
<b>Streaming video (remote display)</b>	Via HDMI; GigE Ethernet available in SmartView® software in 2015			Via USB or WiFi	
<b>Remote control</b>	Yes. Available in 2015			Yes	—
<b>Alarms</b>	High-temperature, low-temperature, and isotherm color alarms				
<b>Warranty</b>	2 years (standard), extended warranties are available				

<sup>1</sup> Fluke Connect™ not available in all countries

<sup>2</sup> Add-on at time of order—subwindowing options are not available on 9 Hz models

## More lenses. More options. BETTER RESULTS.

Field swappable lenses can make your camera work better for your application. Capture spectacular images in challenging situations and gain greater insight through the use of a specialized lenses. Super-wide angle to super telephoto and three macro lenses—when you need ultimate flexibility.



**Contact your local Fluke  
representative for more  
information on these  
REMARKABLE  
INFRARED CAMERAS.**

# Fluke infrared cameras are **ON THE JOB** because they **DO THE JOB.**



## EXPERT SERIES

Engineers, R&D professionals and advanced thermographers who require premium image quality and an excellent level of detail in every infrared image.


- Industrial maintenance
- Utilities
  - Transmission/distribution
- Oil and gas predictive maintenance
- Research and development
  - Electrical
  - Mechanical
  - Biology/sciences
- Quality control



## PROFESSIONAL SERIES

Professional in-house, contract and service thermographers who need superior quality images and advanced features and specifications for use in multiple applications.

- Industrial maintenance
- Heavy commercial facility maintenance
- Oil and gas maintenance
- Veterinary
- Reliability inspections



## PERFORMANCE SERIES

Technicians and contractors who need quality images and feature rich affordability for quick scans and/or intermittent inspections.

- Electrical
- HVAC
- Mechanical
- Home inspections
- Light commercial maintenance
- Building diagnostics
  - Building envelope
  - Commercial/industrial facilities

See HD infrared in action at [FLUKE.COM/EXPERTSERIES](http://FLUKE.COM/EXPERTSERIES)

**Fluke.** Keeping your world up and running.®

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**Fluke Europe B.V.**  
PO Box 1186, 5602 BD  
Eindhoven, The Netherlands

**Modification of this document is not permitted without written permission from Fluke Corporation.**

Smart phone, wireless service and data plan not included with purchase. First 5 GB of storage is free. Compatible with iPhone 4x and up running iOS 7 or higher, iPad (in an iPhone frame on iPad), Samsung Galaxy S4 running Android 4.3.x or higher and Samsung Galaxy S, Nexus 5, HTC One and One M8 running Android™ 4.4.x or higher. Apple and the Apple logo are trademarks of Apple Inc. registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Google Play is a trademark of Google Inc.

**For more information call:**  
In the U.S.A. (800) 443-5853 or  
Fax (425) 446-5116  
In Europe/M-East/Africa +31 (0)40 267 5100 or  
Fax +31 (0)40 267 5222  
In Canada (800)-36-FLUKE or  
Fax (905) 890-6866  
From other countries +1 (425) 446-5500 or  
Fax +1 (425) 446-5116  
Web access: <http://www.fluke.com>

©2014 Fluke Corporation.  
Specifications subject to change without notice.  
Printed in U.S.A. 12/2014 6004356a-en



Built with  
**FLUKE CONNECT™**  
See it. Save it. Share it.™

Download the app



Fluke Connect is not available in all countries.