

PSP-603/405/2010



FEATURES

* LCD Display

- * Output ON/OFF Control
- * 3 Step Fan Speed Control
- * Voltage/Current/Power Setting
- * Key Lock to Avoid Error Operation
- * Normal , +% & -% Output Operation Key
- * Standard Interface : RS-232C
- * Optional European Type Jack Terminal

Rear Panel



The PSP-Series are single output, 200W, programmable switching DC power supplies. OVP, OCP, OTP, and OPP protect the PSP-Series and its loads from unexpected conditions. The PSP-Series have large a LCD panel with output and parameter views and a key lock feature to prevent changing the settings. The PSP-Series is suitable for generic bench-top applications in laboratories and educational institutions.

SPECIFIC/	ATIONS				
OUTPUT Model		PSP-603	PSP-405	PSP-2010	
Voltage		0 ~ 60V	0 ~ 40V	0 ~ 20V	
Current		0 ~ 3.5A	0 ~5A	0 ~ 10A	
VOLTAGER	EGULATION	1		1	
Load		\leq 10mV	\leq 10mV	\leq 10mV	
Line		≤ 0.05%	≤ 0.05%	[≤] 0.05%	
CURRENT F	REGULATION	·		L	
Load		\leq 5mA	< 5mA	< 5mA	
Line		< 0.05%	$\stackrel{\leq}{=}$ 5mA $\stackrel{\leq}{=}$ 0.05%	< 0.05%	
RIPPLE					
	a\/####\$	< 20mV	< 20mV	5 20	
Voltage (n		$\leq 10 \text{mA}$	$\leq 10 \text{mV}$	$\leq 20 \text{mV}$ $\leq 10 \text{mA}$	
Current (mArms)		I0mA	10mA	10mA	
RESOLUTIO	DN	1		T	
Voltage		20mV	10mV	10mV	
Current		2mA	2mA	5mA	
PROGRAM	ACCURACY	1		T	
Voltage		± 0.05%rdg±4digits	<u>+</u> 0.05%rdg <u>+</u> 3digits	\pm 0.05%rdg \pm 3digits	
Current		<u>+</u> 0.1%rdg + 5digits	<u>+</u> 0.1%rdg + 5digits	<u>+</u> 0.3%rdg + 10digits	
READBACK	(METER) RESOLUTI	ON			
Voltage		Same as Resolution	Same as Resolution	Same as Resolution	
Current		Same as Resolution	Same as Resolution	Same as Resolution	
	(METER) ACCURAC			1	
Voltage		Same as Program Accuracy	Same as Program Accuracy	Same as Program Accurac	
Current		Same as Program Accuracy	Same as Program Accuracy	Same as Program Accurac	
		V	V	V	
-	/OPP/OTP	v	•	•	
OUTPUT C	N/OFF CONTROL	V	V	V	
DISPLAY		•	•	•	
LCD					
	(STANDARD)				
RS-232C					
POWER SO	URCE				
AC 115V+10	0% , AC 230V <u>+</u> 15%,	50/60Hz			
DIMENSIO	NS & WEIGHT	,			
	(H) x 305(D) mm ; App	rox. 4kg			
		•			
ORDERING INFORMATION					
PSP-603	SP-603 200W Programmable Switching DC Power Supply				
	200W Programmable Switching DC Power Supply				
ACCESSOR	IES :				
User manual x 1, Power cord x 1, Test lead GTL-104 x 1 , European test lead GTL-204 x 1					

OPTIONAL ACCESSORIES

GTL-232A RS-232C Cable FREE DOWNLOAD

PC Software RS-232 Remote Control Software