ΗΙΟΚΙ

World's First

DC HIGH VOLTAGE PROBE P2000

Safe Inspection of Photovoltaic Power Generation Facilities with Increasingly High Voltage

Photovoltaic power generation equipment are becoming increasingly high-voltage in order to reduce costs and improve the efficiency of power generation systems. As a result, it is important to select measuring instruments that support higher voltage measurement to protect the safety of inspection workers.

The P2000 enables high voltage measurement up to CAT III 2000 V by simply connecting to a compatible HIOKI clamp meter or digital multimeter.



P2000 Specifications

Maximum input voltage (max. rated voltage between INPUT H-INPUT L)	DC 2000 V
Maximum rated voltage to earth	2000 V (Measurement Category III) 1000 V (Measurement Category IV)
Input resistance	20 M Ω ±1.0% (between INPUT H – INPUT L)
Output ratio	Depends on the input impedance of the connected device (example: $1/10$ when a device with an input impedance of $10 M\Omega$ is connected)
Overload protection	DC/AC 2200 V 1 minutes (between INPUT H – INPUTO L) DC/AC 600 V 1 minutes (between OUTPUT H – OUTPUT L)
Secondary terminal	4 mm banana terminal
Operating environment	Indoor use, pollution degree 2, altitude up to 2000 m
Operating tempera- ture and humidity range	Temperature: -25°C to 65°C Humidity: -25°C to 40°C, up to 80% RH (non-condensing) 40°C to 65°C, (the operation humidity limit falls linearly from 40°C 80% RH to 65°C 25% RH, given that there is no condensation)
Storage temperature and humidity range	-30° C to 70° C 90% RH or less (non-condensing)
Applicable standards	Safety EN 61010

Product warranty period	3 years (probe body and cable part are not covered by warranty)
Accessories	L4943 connection cable, Strap belt, Strap buckle x2, C0205 carrying case, "Instruction Manual", "Usage Precautions"

Accuracy in combination with the DT4261 or CM series

Models	Combination Accuracy Specifications (Representative value)
DT4261	±0.5% rdg. ±5 dgt.
CM4375-50	±1.0% rdg. ±3 dgt.
CM4373-50	
CM4371-50	
CM4141-50	

Model

Model : AC HIGH VOLTAGE PROBE P2000

Model No. (Order Code) P2000

P2000 Compatible Models



DIGITAL MULTIMETER DT4261



AC/DC CLAMP METER CM4375-50

DISTRIBUTED BY



AC/DC CLAMP METER CM4373-50



AC/DC CLAMP METER CM4371-50



AC CLAMP METER CM4141-50



HIOKI E.E. CORPORATION

HEADQUARTERS

81 Koizumi, Ueda, Nagano 386-1192 Japan https://www.hioki.com/



Scan for all regional contact information